

ESP-72/WS - PA Wall Speaker



PA wall speaker

- 100 V line technique
- 2-way coaxial speaker, providing a high-quality sound
- 5-step rotary switch for 20/10/5/2.5 W/off
- Rotary switch can be replaced with a cover plate to avoid accidental changing of the power selection
- Emergency priority relay
- White wooden cabinet with protective metal grille
- Mounting plate for easy wall mounting
- Ball-proof according to DIN 18032, Part 3

Tekniske data

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 20/10/5/2.5 W
Impedance	: -
Frequency range	: 85-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: -
Speaker size	: -
Sensitivity	: -
Max. rated SPL	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: wood
Colour	: white
Mounting device	: mounting plate
Protected against ball rebound	: yes
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 300 x 200 x 90 mm
Width	: 300 mm
Height	: 200 mm
Depth	: 90 mm
Weight	: 2.8 kg



Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -