


SA-130DMP - Amplifier



Stereo amplifier, 140 W

with integrated MP3 player, Bluetooth receiver, FM radio, USB interface and SD/MMC card slot.

- Bluetooth receiver for wireless connection of laptops, smartphones or tablet PCs
- USB storage media can be connected directly
- For SD/MMC cards up to 32 GB (FAT16/FAT32), available at option
- Adjustable microphone input and aux input on the front panel
- Adjustable stereo line input
- Insert facility, e.g. for effect units, equalizers, feedback controllers
- 2-way tone control
- Adjustable master output
- 482 mm (19") rack installation, 1 RS

Tekniske data

Peak output power	: -
Power rating	: 140 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 70 W
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 480 mV/20 kOhm (line)1.3 mV/500 Ohm (mic)190 mV/10 kOhm (aux)580 mV/22 kOhm (amp in)
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 12 dB/100 Hz
Equalizer midrange	: -
Equalizer treble	: ± 10 dB/10 kHz
S/N ratio	: 90 dB
Crosstalk attenuation	: -
THD	: 0.1%
Mains voltage	: \approx 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 350 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C

Width : 482 mm
Height : 44 mm
Depth : 245 mm





Rack spaces, RS	: 1
Weight	: 4.9 kg
Connections	: 1 x RCA L/R (line), 1 x XLR/6.3 mm jack (mic), 1 x 3.5 mm jack (aux), 1 x RCA L/R (amp in), 1 x RCA L/R (amp out), screw terminals (speakers)