

ICM-20H - Intercom



Intercom system, cable-connected, consisting of desktop microphone and separate call station. Ideally suited, e.g. for reception desks and sales counters.

Desktop microphone:

- 300 mm gooseneck, removable (XLR connection)
- Electret microphone cartridge, cardioid polar pattern
- Built-in amplifier and speaker
- Volume control
- Push-to-talk button
- Headphone connection (3.5 mm jack) with automatic switch-off of the built-in speaker
- Power is provided via enclosed power supply
- Dimensions console housing: 115 x 65 x 170 mm

Call station:

- Built-in speaker and microphone
- Call button (buzzer)
- 3 m connection cable for connection to desktop microphone
- Supplied with mounting accessories for attachment to glass panels
- Power supply via desktop microphone
- Dimensions: Ø 85 mm x 35 mm

Tekniske data

| | |
|-------------------------|---|
| Description | : desktop microphone with call station |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : cardioid |
| System | : electret |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : via encl. power supply |
| Operating time | : - |
| Audio frequency range | : - |
| Nominal impedance | : - |
| Sensitivity | : - |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : 300 mm |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : 115 x 65 x 170 mm (console housing), 85 mm x 35 mm (call station) |
| Weight | : 0.98 kg |
| Cable | : 3 m |
| Connection | : 2 x RCA, 1 x 3.5 mm jack |