

## PA-4000RC - PA Desk Microphone



PA 4-zone paging desktop microphone,  
for connection to PA-40120 and PA-6040MPX.

- Selection buttons for 4 zones, for activating one or several zones
- ALL CALL button for activating all of the 4 zones
- Autom. chime via microphone announcement button (talk)
- LED status indication for the zone buttons (busy, emergency), power, mic fault, signal and talk
- Built-in gooseneck electret microphone
- Adjustable microphone sensitivity
- Chime can be activated or deactivated as required
- 24 V power supply via PA-40120 or PA-6040MPX
- Two RJ45 jacks for connection to PA-40120, PA-6040MPX or optional power supply and additional microphones PA-4000RC
- Supplied with connection module for PA-40120 and PA-6040MPX
- Up to 32 x PA-4000RC can be connected to PA-40120 or PA-6040MPX via bus
- Supplied with 3 m connection cable (Cat. 5e)

## Tekniske data

|                         |  |
|-------------------------|--|
| Description             | : PA desktop microphone                                  |
| Version                 | : -  |
| Transmission method     | : cable  |
| Polar pattern           | : -  |
| System                  | : -  |
| Carrier frequency range | : -  |
| Transmitting power      | : -  |
| Power supply            | : via PA-40120, PA-6040MPX or optional 24 V power supply |
| Operating time          | : -  |
| Audio frequency range   | : -  |
| Nominal impedance       | : -  |
| Sensitivity             | : -  |
| S/N ratio               | : -  |
| Max. sound pressure     | : -  |
| Power supply            | : -  |
| Gooseneck length        | : -  |
| Housing material        | : -  |
| Admiss. ambient temp.   | : 0-40 °C  |
| Dimensions              | : -  |
| Weight                  | : 0.9 kg   |
| Cable                   | : Cat. 5e, 3 m   |
| Connection              | : 2 x RJ45   |