

## HPR-6 - Headphones Amplifier



Efficient stereo headphone amplifier,  
can also be used as a small power amplifier for 4-8 Ohm speaker systems

- Robust metal housing
- Stereo RCA input
- 6.3 mm stereo output
- Volume control and balance control

## Tekniske data

|                       |  |
|-----------------------|--|
| Description           | : stereo headphone amplifier   |
| Frequency range       | : 19-40,000 Hz   |
| Control range         | : -  |
| Control frequencies   | : -  |
| Input signal          | : 110 mV-4 V   |
| Input sensitivity     | : -  |
| Input impedance       | : -  |
| Output signal         | : 2 x 525 mW/2 x 1,500 mW/4 Ohm, 2 x 330 mW/2 x 750 mW/8 Ohm, 2 x 114 mW/2 x 200 mW/32 Ohm |
| Output impedance      | : -  |
| Gain                  | : -  |
| Phantom power         | : -  |
| Compression           | : -  |
| Gate ratio            | : -  |
| Crossover frequency   | : -  |
| High-pass filter      | : -  |
| Low cut               | : -  |
| Transmission ratio    | : -  |
| S/N ratio             | : 69 dB  |
| Channel separation    | : -  |
| THD                   | : 1%   |
| Admiss. ambient temp. | : 0-40 °C  |
| Power supply          | : via encl. plug-in power supply   |
| Dimensions            | : 120 x 68 x 36 mm   |
| Weight                | : 288 g  |
| Inputs                | : 2 x RCA L/R  |
| Outputs               | : 1 x 6.3 mm jack  |
| Other features        | : -  |