

EPS110/RS485 - MP3 spiller DIN



MP3 player,
event-driven.

- For mounting onto DIN rails according to DIN EN 60715, 2 HP
- For SDHC/SD/MMC cards up to 32 GB (FAT32), available at option
- Extensive playback functions
- 7 binary inputs and outputs
- In/Out string triggers
- Interface for communication
- Decentral extensions
- Connection for EIB push-button sensor
- DMX interface (optional)
- Stereo line output, headphone output
- Delay function up to 4 hours
- Free configuration software
- Firmware update possible

Tekniske data

| | |
|------------------------------------------|-------------------------------|
| Description | : MP3 player |
| Media | : MP3, WAV |
| Frequency range | : 18-20,000 Hz |
| THD | : 0.001% |
| Channel separation | : - |
| Dynamic range | : - |
| S/N ratio | : - |
| Output, analogue | : 2 V/600Ω Ohm |
| Output, digital, U _{pp} | : - |
| Power supply | : - |
| Mains voltage | : - |
| Mains frequency | : - |
| Power consumption, operation | : - |
| Power consumption, standby | : - |
| Operating voltage (possible alternative) | : 7-24 V |
| Power supply (possible alternative) | : 60 mA (7 V) 25 mA (24 V) |
| Admiss. ambient temp. | : -35-+55 °C |
| Dimensions | : 74 x 113 x 35 mm |
| Dim., player mech. | : - |
| Dim., control panel | : - |
| Weight | : 96 g |
| Connections | : 7 binary inputs and outputs |
| Packing dimensions (W x H x L) | : 0.037 x 0.095 x 0.075 m |
| Gross weight | : 0.1155 kg |