

SPE-230/WS - Loudspeaker Pair



Pair of flush-mount speakers,
coaxial system, 8 Ohm, tweeter with ferrofluid.

- Moisture-proof
- White one-piece plastic design and plastic cone
- Versatile use for car hi-fi, PA, terrace, boat

Tekniske data

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: 100-20,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 25 W
Peak music power output (MAX)	: 50 W
Sensitivity	: 85 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: \varnothing 110 mm
Mounting depth	: 50 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: \varnothing 150 mm x 66 mm
Outside diameter	: \varnothing 150 mm
Width	: \varnothing 150 mm



Height	: -
Depth	: 66 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.5 kg
Packing unit	: 2
Type of speaker	: 130