

MMX-602/SW - Mixer



Microphone line mixer,
6 channels.

- 6 stereo line inputs, 6 balanced mono microphone inputs, switchable
- Adjustable automatic talkover (-12 dB), switchable for channel 1 or channels 1+2
- Balance control for each stereo input channel
- 3-way equalizer
- 12 V phantom power can be activated as required
- LED VU meter, peak LED
- Master output and record output
- Output can be switched stereo/mono
- Adjustable headphone output
- 482 mm (19") rack installation, 1 RS

Tekniske data

No. of channels	: -
No. of inputs	: -
Mic input	: 1 \hat{A} mV/6.6 \hat{A} kOhm, 6 x 3-pole XLR, bal.
Line input	: 100 \hat{A} mV/10 \hat{A} kOhm, 6 x RCA L/R
CD input	: -
Phono input	: -
Tape (play)	: -
Aux input	: -
Insert input	: -
Effect return	: -
Master output	: 1 \hat{A} V/600 \hat{A} Ohm, 1 x RCA L/R 1 x 3-pole XLR L/R, bal.
Record output	: 310 \hat{A} mV/600 \hat{A} Ohm, 1 x RCA L/R
Monitor output	: -
Booth output	: -
Aux output	: -
Insert output	: -
Effect send	: -
Control room	: -
Tape (rec)	: -
Headphones	: ? \hat{A} 8 \hat{A} Ohm, 1 x 6.3 mm jack
Gooseneck lamp	: -
WiFi	: -
USB	: -
Bluetooth	: -
Frequency range	: 20-20,000 Hz
THD	: 0.1%
S/N ratio	: 62 \hat{A} dB, unweighted
Crosstalk	: -
Equalizer bass	: \pm 12 \hat{A} dB/50 \hat{A} Hz
Equalizer midrange	: \pm 12 \hat{A} dB/1 \hat{A} kHz
Equalizer treble	: \pm 12 \hat{A} dB/10 \hat{A} kHz
equalizer	: -
Talkover	: -12 dB, manual
Phantom power	: -
Crossfader	: -

Media player	: -
Amplifier	: -
Power supply	: ∿ 230Â V/50Â Hz/12Â VA
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 12 VA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 47 mm
Depth	: 208 mm
Rack spaces, RS	: 1
Weight	: 2.8 kg