

MPR-6 - Microphone Pre-Amplifier



Microphone preamplifier,
for connecting up to 2 microphones to one line input.

- Stereo or 2 x mono
- Wide frequency range
- Black metal case
- Supplied with plug-in power supply

Microphone preamplifier,
for connecting up to 2 microphones to a line input of a hi-fi system, an amplifier or a mixer.

- Stereo or 2 x mono
- Wide frequency range
- Black metal case
- Supplied with plug-in power supply

Tekniske data

Description	: microphone preamplifier
Frequency range	: 5-40,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: 2Â mV/1Â V output
Input sensitivity	: -
Input impedance	: 10 kOhm
Output signal	: max. 3.2Â V/47Â kOhm
Output impedance	: -
Gain	: 53 dB
Phantom power	: -
Compression	: -
Gate ratio	: -
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: -
S/N ratio	: 63 dB
Channel separation	: -
THD	: 0.05%
Admiss. ambient temp.	: 0-40 °C
Power supply	: via encl. plug-in power supply
Dimensions	: 67 x 37 x 121Â mm
Weight	: 215 g
Inputs	: 2 x 6.3mm jack
Outputs	: 2 x RCA
Other features	: -