

WALL-05DTM/WS - 2-Way Dante Speaker Cabinet



Active speaker with integrated Dante(r) module

- 2-way system
- 13 cm (5") bass-midrange speaker and 13 mm (½") tweeter
- Mounting bracket for pivoting and tilting
- Power supply via PoE (Power over Ethernet) or via optional power supply (19 V/2.5 A)

System requirements Dante(r): Windows 7/8.1/10/11 or MacOS 10.9.5/10.10.5/10.11

The brand Dante(r) as well as the Dante(r) software which may have been integrated into these products are licenced by Audinate Pty Ltd.

Tekniske data

| | |
|--------------------------------|------------------------|
| Active/passive | : active |
| Transmission technology | : Dante ^(r) |
| Total output power | : - |
| Power rating (RMS) | : 30 W |
| Total power rating | : - |
| Power rating (RMS) | : - |
| Impedance | : - |
| Frequency range | : 62-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : |
| Full range speaker | : - |
| Bass speaker | : |
| Midrange speaker | : - |
| Tweeter | : |
| Number of speakers | : 2 |
| Speaker size | : 13 cm |
| SPL | : 89 dB/W/m |
| Max. rated SPL | : 105 dB |
| Beam angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : |
| Colour | : |
| Mounting device | : |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : |
| Dimensions | : |
| Width | : 163 mm |
| Height | : 252 mm |
| Depth | : 165 mm |



| | |
|--------------------------------|-----------|
| Weight | : 2.12 kg |
| Inputs | : |
| Outputs | : |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : |
| Gross weight | : 2.72 kg |
| Net weight | : 2.44 kg |