

## PA-1200M - Monitor Unit



Monitor unit, 10 + 1 channels

- Audio sources can be selected via rotary switch
- 10 monitor inputs 1-100 V/10 kOhm
- 1 aux input 0 dB (0.775 V)/600 Ohm
- Level control, LED VU meter and clip LED for each monitor input
- Built-in 2 W speaker, volume control
- Headphone output
- Mains operation and 24 V emergency power operation

## Tekniske data

Peak output power	: -
Power rating	: 2 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 11
Zones	: -
Inputs	: 1-100 V/10 kOhm (monitor)0.775 V/600 Ohm (aux)
Attenuation factor	: -
Frequency range	: 100-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: -
Crosstalk attenuation	: -
THD	: < 0.3%
Mains voltage	: DC 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 15 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 24 V
Power supply (possible alternative)	: 0.5 A
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 88 mm

Depth

: 200 mm





---

Rack spaces, RS	: 2
Weight	: 4.7 kg
Connections	: screw terminals (monitor input 1-10),screw terminals (aux input), 6.3 mm jack (headphones)