

SPL-6 - Limiter



2-channel limiter,
with measuring microphone and timer function.

- Adjustable via threshold and output
- dB(A), dB(C) and dB peak
- 10-band equalizer
- 10-band limiter
- 64 days memory
- Time slot, 3 different limitings possible each day
- Can be remote controlled via Internet
- An installation licence is required for setting up
- Connection facility for external display SPL-D2
- XLR inputs and outputs
- Microphone input

Tekniske data

| | |
|-----------------------|---|
| Description | : 2-channel limiter |
| Frequency range | : 5-22,000 Hz |
| Control range | : - |
| Control frequencies | : - |
| Input signal | : - |
| Input sensitivity | : 6 V |
| Input impedance | : 50 kOhm |
| Output signal | : - |
| Output impedance | : 50 Ohm |
| Gain | : - |
| Phantom power | : - |
| Compression | : - |
| Gate ratio | : - |
| Crossover frequency | : - |
| High-pass filter | : - |
| Low cut | : - |
| Transmission ratio | : - |
| S/N ratio | : ? 80 dB |
| Channel separation | : - |
| THD | : < 0.06% |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : ∿ 100-240 V/50 HZ/15 W |
| Dimensions | : 482 x 45 x 175 mm |
| Weight | : 2.7 kg |
| Inputs | : 2 x XLR, bal. (line), 1 x XLR (measuring microphone) |
| Outputs | : 2 x XLR, bal. (line) |
| Other features | : threshold: 70-120 dB(A), output correction: -50 to +18 dB, microphone correction: -40 to +18 dB, maximum adjustment range: -6 to -50 dB |