

EDL-530EN/SW - PA Loudspeaker



High-quality PA pendant speaker,
with EN 54-24 certification.

- 100 V line technique or 8 Ohm operation
- 2-way coaxial system (5.25")
- UV-resistant ABS housing with aluminium grille
- Excellent sound quality for speech and music
- 5 m safety rope
- Plug-in screw terminal

Tekniske data

| | |
|--------------------------------|---|
| Active/passive | : passive |
| Transmission technology | : 100 V or low-impedance |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 30/15/7.5/3.8 W |
| Impedance | : 8 Ohm |
| Frequency range | : 65-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : 2-way coaxial |
| Full range speaker | : - |
| Bass speaker | : 13.33 cm (5.25") |
| Midrange speaker | : - |
| Tweeter | : 25 mm (1") |
| Number of speakers | : 2 |
| Speaker size | : 13.33 cm (5.25") |
| SPL | : 90 dB/W/m |
| Max. rated SPL | : - |
| Beam angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : ABS |
| Colour | : black |
| Mounting device | : Eyelet bolt and 5 m steel rope with snap hook |
| Protected against ball rebound | : - |
| Protection class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : Å~ 195 mm x 250 mm |
| Width | : Å~ 195 mm |
| Height | : 250 mm |
| Depth | : - |



| | |
|--------------------------------|--------------------------|
| Weight | : 2.26 kg |
| Inputs | : plug-in screw terminal |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.22 x 0.3 x 0.22 m |
| Gross weight | : 2.66 kg |
| Net weight | : 2.26 kg |