

## EDL-530EN/WS - PA Loudspeaker



High-quality PA pendant speaker,  
with EN 54-24 certification.

- 100 V line technique or 8 Ohm operation
- 2-way coaxial system (5.25")
- UV-resistant ABS housing with aluminium grille
- Excellent sound quality for speech and music
- 5 m safety rope
- Plug-in screw terminal

## Tekniske data

|                                |  |
|--------------------------------|--|
| Active/passive                 | : passive  |
| Transmission technology        | : 100 V or low-impedance                         |
| Total output power             | : -  |
| Power rating (RMS)             | : -  |
| Total power rating             | : -  |
| Power rating (RMS)             | : 30/15/7.5/3.8 W                                |
| Impedance                      | : 8 Ohm  |
| Frequency range                | : 65-20,000 Hz                                   |
| THD                            | : -  |
| S/N ratio                      | : -  |
| Input signal                   | : -  |
| System                         | : 2-way coaxial                                  |
| Full range speaker             | : -  |
| Bass speaker                   | : 13.33 cm (5.25")                               |
| Midrange speaker               | : -  |
| Tweeter                        | : 25 mm (1")                                     |
| Number of speakers             | : 2  |
| Speaker size                   | : 13.33 cm (5.25")                               |
| SPL                            | : 90 dB/W/m                                      |
| Max. rated SPL                 | : -  |
| Beam angle                     | : -  |
| Radiation angle, horizontal    | : -  |
| Radiation angle, vertical      | : -  |
| Features                       | : -  |
| Housing material               | : ABS  |
| Colour                         | : white  |
| Mounting device                | : eyelet bolt and 5 m safety rope with snap hook |
| Protected against ball rebound | : -  |
| Protection class               | : -  |
| Admiss. ambient temp.          | : 0-40 °C  |
| Power supply                   | : -  |
| Dimensions                     | : Å~ 195 mm x 250 mm                             |
| Width                          | : Å~ 195 mm                                      |
| Height                         | : 250 mm   |
| Depth                          | : -  |



|                                |                          |
|--------------------------------|--------------------------|
| Weight                         | : 2.26 kg                |
| Inputs                         | : plug-in screw terminal |
| Outputs                        | : -                      |
| Replacement voice coil         | : -                      |
| Other features                 | : -                      |
| Accessories                    | : -                      |
| Packing dimensions (W x H x L) | : 0.22 x 0.3 x 0.22 m    |
| Gross weight                   | : 2.66 kg                |
| Net weight                     | : 2.26 kg                |