

ESP-1000AB - PA Wall-/Ceiling Speaker



PA A/B wall speaker,
with EN 54-24 certification for evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 2 x 10 cm full range speaker
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Plastic cabinet with open rear panel with protective metal front grille
- Supplied with aluminium mounting bracket, screws and wall plugs

Tekniske data

Active/passive	: passive
Transmission method	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 2 x 6/3/1.5 W
Impedance	: -
Frequency range	: 80-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: 2 x 10 cm
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 2
Speaker size	: 10 cm
Sensitivity	: 92 dB/W/m
Max. rated SPL	: 100 dB
Radiation angle, horizontal	: 160°
Radiation angle, vertical	: 160°
Features	: -
Housing material	: metal
Colour	: white
Mounting device	: bracket
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: -10 °C to +50 °C
Power supply	: -
Dimensions	: 220 mm x 100 mm
Width	: 220 mm
Height	: -
Depth	: 100 mm
Weight	: 1.98 kg



Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -